

Robust Hybrid Feedback Control Design for Networked Systems

Ricardo Sanfelice

Department of Computer Engineering
Hybrid Systems Laboratory
University of California, Santa Cruz



Prevalent Network Control Applications

Control of Groups of Neurons

[ACC 14, TCNS 16]

*Multi-agent Systems with Limited
Information* [TCNS 16, Automatica 16]

*Coordination of
Underactuated Vehicles*

[Automatica 15, TAC 16]

Prevalent Network Control Applications

Control of Groups of Neurons

[ACC 14, TCNS 16]

Multi-agent Systems with Limited Information [TCNS 16, Automatica 16]

Key Features:

- ▶ Nonlinearities
- ▶ Fast time scales / events
- ▶ Limited information

Motivation and Approach

Common features in applications:

- ▶ Variables changing continuously (e.g., physical quantities) and discretely (e.g., logic variables, resetting timers).
- ▶ Abrupt changes in the dynamics (changes in the environment, control decisions, communication events, or failures).

Motivation and Approach

Common features in applications:

- ▶ Variables changing continuously (e.g., physical quantities) and discretely (e.g., logic variables, resetting timers).
- ▶ Abrupt changes in the dynamics (changes in the environment, control decisions, communication events, or failures).

Driving Question:






How can we systematically design such systems with provable robustness to uncertainties arising in real-world environments?

Approach:

- ▶ Capture continuous and discrete behavior using dynamical modeling.
- ▶ Analysis of stability and control design using control theoretical tools.
- ▶ Numerical (and sometimes experimental) validation.

Recent Contributions to Hybrid Systems Theory

- ▶ Autonomous Hybrid Systems
 - ▶ Notion of Solution
 - ▶ Lyapunov Theory and Invariance
 - ▶ Robustness to Small Perturbations
- ▶ Nonautonomous Hybrid Systems
 - ▶ Notion of Solution
 - ▶ Control Lyapunov Functions
 - ▶ I/O Stability
 - ▶ Interconnections
 - ▶ Small gain Theorems
- ▶ Hybrid Control Design
 - ▶ Minimum-norm Control
 - ▶ Passivity-based Control
 - ▶ Backstepping
 - ▶ Tracking Control
- ▶ Numerical Simulation
 - ▶ Simulation theory
 - ▶ Simulation toolbox



Outline

1. Introduction

- ▶ Motivation, Approach, and Recent Contributions
- ▶ Prevalent Network Control Applications

Outline

1. Introduction

- ▶ Motivation, Approach, and Recent Contributions
- ▶ Prevalent Network Control Applications

2. Hybrid Systems Tools for Control of Networks

- ▶ Hybrid Inclusion Models
- ▶ Lyapunov Stability Tools
- ▶ Robustness Tools
- ▶ Applications to Network Estimation and Synchronization

Outline

1. Introduction

- ▶ Motivation, Approach, and Recent Contributions
- ▶ Prevalent Network Control Applications

2. Hybrid Systems Tools for Control of Networks

- ▶ Hybrid Inclusion Models
- ▶ Lyapunov Stability Tools
- ▶ Robustness Tools
- ▶ Applications to Network Estimation and Synchronization

3. Conclusion

Outline

1. Introduction

- ▶ Motivation, Approach, and Recent Contributions
- ▶ Prevalent Network Control Applications

2. Hybrid Systems Tools for Control of Networks

- ▶ Hybrid Inclusion Models
- ▶ Lyapunov Stability Tools
- ▶ Robustness Tools
- ▶ Applications to Network Estimation and Synchronization

3. Conclusion

Related Work

A (rather incomplete) list of related contributions:

- ▶ Differential equations with multistable elements

[Witsenhausen - TAC 66]

- ▶ Differential automata

[Tavernini - NA 87]

- ▶ Hybrid automata

[Branicky et al. - TAC 98]

[van der Schaft and Schumacher 00]

[Lygeros et al. - TAC 01]

Related Work

A (rather incomplete) list of related contributions:

- ▶ Differential equations with multistable elements
[Witsenhausen - TAC 66]
- ▶ Differential automata
[Tavernini - NA 87]
- ▶ Hybrid automata
[Branicky et al. - TAC 98]
[van der Schaft and Schumacher 00]
[Lygeros et al. - TAC 01]
- ▶ Impulsive differential equations
[Bainov and Simeonov 89]
[Chellaboina et al. - NA 03]


Related Work

A (rather incomplete) list of related contributions:


- ▶ Differential equations with multistable elements
[Witsenhausen - TAC 66]
- ▶ Differential automata
[Tavernini - NA 87]
- ▶ Hybrid automata
[Branicky et al. - TAC 98]
[van der Schaft and Schumacher 00]
[Lygeros et al. - TAC 01]
- ▶ Impulsive differential equations
[Bainov and Simeonov 89]
[Chellaboina et al. - NA 03]
- ▶ Measure-driven differential equations
[Moreau 88]
[Silva and Vinter - J. Math. Anal. Appl. 96]
- ▶ Systems with unilateral constraints
[Brogliato 96]
- ▶ \vdots

Modeling Trajectories


Modeling Trajectories




Modeling Trajectories




Modeling Trajectories



Modeling Trajectories



Modeling Trajectories



Modeling Hybrid Systems

Hybrid systems are given by *hybrid inclusions*

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & = f(x, u) & (x, u) \in C \\ x^+ & = g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

where x is the *state*, u the *input*, y the *output*

▶ C is the *flow set*

▶ D is the *jump set*

▶ f is the *flow map*

▶ g is the *jump map*

and h is the *output map*.

Modeling Hybrid Systems

Hybrid systems are given by *hybrid inclusions*

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

where x is the *state*, u the *input*, y the *output*

▶ C is the *flow set*

▶ D is the *jump set*

▶ f is the *flow map*

▶ g is the *jump map*

and h is the *output map*.

Modeling Hybrid Systems

Hybrid systems are given by *hybrid inclusions*

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

where x is the *state*, u the *input*, y the *output*

- ▶ C is the *flow set*
- ▶ D is the *jump set*
- ▶ f is the *flow map*
- ▶ g is the *jump map*

and h is the *output map*.

Solutions are functions parameterized by hybrid time (t, j) :

- ▶ **Flows** parameterized by $t \in \mathbb{R}_{\geq 0} := [0, +\infty)$
- ▶ **Jumps** parameterized by $j \in \mathbb{N}_{\geq 0} := \{0, 1, 2, \dots\}$

Modeling Hybrid Systems

Hybrid systems are given by *hybrid inclusions*

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

where x is the *state*, u the *input*, y the *output*

- ▶ C is the *flow set*
- ▶ D is the *jump set*
- ▶ f is the *flow map*
- ▶ g is the *jump map*

and h is the *output map*.

Solutions are functions parameterized by hybrid time (t, j) :

- ▶ **Flows** parameterized by $t \in \mathbb{R}_{\geq 0} := [0, +\infty)$
- ▶ **Jumps** parameterized by $j \in \mathbb{N}_{\geq 0} := \{0, 1, 2, \dots\}$

Then, solutions to \mathcal{H} are given by pairs (x, u) defined on

$$([0, t_1] \times \{0\})$$

Modeling Hybrid Systems

Hybrid systems are given by *hybrid inclusions*

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

where x is the *state*, u the *input*, y the *output*

- ▶ C is the *flow set*
- ▶ D is the *jump set*
- ▶ f is the *flow map*
- ▶ g is the *jump map*

and h is the *output map*.

Solutions are functions parameterized by hybrid time (t, j) :

- ▶ **Flows** parameterized by $t \in \mathbb{R}_{\geq 0} := [0, +\infty)$
- ▶ **Jumps** parameterized by $j \in \mathbb{N}_{\geq 0} := \{0, 1, 2, \dots\}$

Then, solutions to \mathcal{H} are given by pairs (x, u) defined on

$$([0, t_1] \times \{0\}) \cup ([t_1, t_2] \times \{1\})$$

Modeling Hybrid Systems

Hybrid systems are given by *hybrid inclusions*

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

where x is the *state*, u the *input*, y the *output*

- ▶ C is the *flow set*
- ▶ D is the *jump set*
- ▶ f is the *flow map*
- ▶ g is the *jump map*

and h is the *output map*.

Solutions are functions parameterized by hybrid time (t, j) :

- ▶ **Flows** parameterized by $t \in \mathbb{R}_{\geq 0} := [0, +\infty)$
- ▶ **Jumps** parameterized by $j \in \mathbb{N}_{\geq 0} := \{0, 1, 2, \dots\}$

Then, solutions to \mathcal{H} are given by pairs (x, u) defined on

$$([0, t_1] \times \{0\}) \cup ([t_1, t_2] \times \{1\}) \cup \dots ([t_j, t_{j+1}] \times \{j\}) \cup \dots$$

Modeling Hybrid Systems

Hybrid systems are given by *hybrid inclusions*

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

where x is the *state*, u the *input*, y the *output*

- ▶ C is the *flow set*
- ▶ D is the *jump set*
- ▶ f is the *flow map*
- ▶ g is the *jump map*

and h is the *output map*.

Solutions are functions parameterized by hybrid time (t, j) :


- ▶ **Flows** parameterized by $t \in \mathbb{R}_{\geq 0} := [0, +\infty)$
- ▶ **Jumps** parameterized by $j \in \mathbb{N}_{\geq 0} := \{0, 1, 2, \dots\}$

Then, solutions to \mathcal{H} are given by pairs (x, u) defined on


$$([0, t_1] \times \{0\}) \cup ([t_1, t_2] \times \{1\}) \cup \dots ([t_j, t_{j+1}] \times \{j\}) \cup \dots$$

The state x can have logic, memory, and timer components.


Modeling Hybrid Systems



General Network Control Setting



General Network Control Setting



- ▶ $\Gamma = (\mathcal{V}, \mathcal{E}, \mathcal{G})$ directed graph
- ▶ $\mathcal{V} := \{1, 2, \dots, N\}$ set of nodes
- ▶ $\mathcal{E} \subset \mathcal{V} \times \mathcal{V}$ set of edges
- ▶ $\mathcal{J}_i = \{k : (i, k) \in \mathcal{E}\}$ neighbors to agent i

- ▶ $\mathcal{G} = \{g_{ik}\}$ is the adjacency matrix, where $g_{ik} = 1$ if $(i, k) \in \mathcal{E}$ and 0 otherwise
- ▶ d_i^{in} and d_i^{out} are the indegree and outdegree of agent i

Estimation Over a Network

Let the dynamics of the i -th node of the network be

$$\dot{z}_i = A_i z_i, \quad y_i = M_i z_i$$

Estimation Over a Network

Let the dynamics of the i -th node of the network be

$$\dot{z}_i = A_i z_i, \quad y_i = M_i z_i$$

Goal

Design of an **observer** for z_i that runs at each of the other agents and measures y_i at **communication event times** $\{t_\ell\}_{\ell=1}^\infty$ satisfying

$$T_1 \leq t_{\ell+1} - t_\ell \leq T_2$$

where

- ▶ T_1 defines the fastest communication rate
- ▶ T_2 represents the Maximum Allowable Transfer Time (MATI)

Estimation Over a Network

Let the dynamics of the i -th node of the network be

$$\dot{z}_i = A_i z_i, \quad y_i = M_i z_i$$

Goal

Design of an **observer** for z_i that runs at each of the other agents and measures y_i at **communication event times** $\{t_\ell\}_{\ell=1}^\infty$ satisfying

$$T_1 \leq t_{\ell+1} - t_\ell \leq T_2$$

where

- ▶ T_1 defines the fastest communication rate
- ▶ T_2 represents the Maximum Allowable Transfer Time (MATI)

Proposed Observer: \hat{z}_k stores the estimate of z_i

$$\begin{aligned} \dot{\hat{z}}_k(t) &= A_i \hat{z}_k(t) && \text{when } t \notin \{t_\ell\}_{\ell=1}^\infty \\ \hat{z}_k^+ &= \hat{z}_k(t) + L_k(y_i(t) - M_i \hat{z}_k(t)) && \text{when } t \in \{t_\ell\}_{\ell=1}^\infty \end{aligned}$$

where L_k is a matrix (gain) to be designed.

Estimation Over a Network

Let the dynamics of the i -th node of the network be

$$\dot{z}_i = A_i z_i, \quad y_i = M_i z_i$$

Goal

Design of an **observer** for z_i that runs at each of the other agents and measures y_i at **communication event times** $\{t_\ell\}_{\ell=1}^\infty$ satisfying

$$T_1 \leq t_{\ell+1} - t_\ell \leq T_2$$

where

- ▶ T_1 defines the fastest communication rate
- ▶ T_2 represents the Maximum Allowable Transfer Time (MATI)

Globally exponentially stabilize the set, denoted \mathcal{A}_{obs} ,
collecting all points such that

$$z_i = \hat{z}_k \quad \forall k \in \mathcal{V}$$

that is, render the **zero estimation error set GES**

Estimation Over a Network – Modeling

Time-varying and (potentially) stochastic system can be modeled as an autonomous hybrid inclusion

Estimation Over a Network – Modeling

Time-varying and (potentially) stochastic system can be modeled as an autonomous hybrid inclusion

Idea: To capture all possible event sequences $\{t_\ell\}_{\ell=1}^\infty$ while removing dependency on time and stochastic dynamics, define

- ▶ τ as a timer that, when expires, generates the communication events from the i -th agent to the k -th agent

Estimation Over a Network – Modeling

Time-varying and (potentially) stochastic system can be modeled as an autonomous hybrid inclusion

Idea: To capture all possible event sequences $\{t_\ell\}_{\ell=1}^\infty$ while removing dependency on time and stochastic dynamics, define

- ▶ τ as a timer that, when expires, generates the communication events from the i -th agent to the k -th agent

with dynamics


$$\begin{cases} \dot{\tau} &= -1 & \tau \in [0, T_2] \\ \tau^+ &\in [T_1, T_2] & \tau = 0 \end{cases}$$

Estimation Over a Network – Modeling

Time-varying and (potentially) stochastic system can be modeled as an autonomous hybrid inclusion

Idea: To capture all possible event sequences $\{t_\ell\}_{\ell=1}^\infty$ while removing dependency on time and stochastic dynamics, define

- τ as a timer that, when expires, generates the communication events from the i -th agent to the k -th agent with dynamics



Estimation Over a Network – Modeling

Time-varying and (potentially) stochastic system can be modeled as an autonomous hybrid inclusion

Idea: To capture all possible event sequences $\{t_\ell\}_{\ell=1}^\infty$ while removing dependency on time and stochastic dynamics, define

- ▶ τ as a timer that, when expires, generates the communication events from the i -th agent to the k -th agent
- ▶ $e = z_i - \hat{z}_k$ as the estimation error used for analysis

Estimation Over a Network – Modeling

Time-varying and (potentially) stochastic system can be modeled as an autonomous hybrid inclusion

Idea: To capture all possible event sequences $\{t_\ell\}_{\ell=1}^\infty$ while removing dependency on time and stochastic dynamics, define

- ▶ τ as a timer that, when expires, generates the communication events from the i -th agent to the k -th agent
- ▶ $e = z_i - \hat{z}_k$ as the estimation error used for analysis

Then, with $x = (e, \tau)$, we have

$$\mathcal{H}_{obs}^{ik} \left\{ \begin{array}{l} \dot{e} = A_i e \\ \dot{\tau} = -1 \end{array} \right\} =: f(x) \quad (e, \tau) \in C$$
$$\left\{ \begin{array}{l} e^+ = (I - L_k M_i) e \\ \tau^+ \in [T_1, T_2] \end{array} \right\} =: g(x) \quad (e, \tau) \in D$$

with the flow set and the jump set defined as

$$C = \mathbb{R}^n \times [0, T_2], \quad D = \{(e, \tau) : \tau = 0\}$$

Synchronization Over a Network

Let the dynamics of each node of the network be

$$\dot{z}_i = Az_i + Bu_i$$

Synchronization Over a Network

Let the dynamics of each node of the network be

$$\dot{z}_i = Az_i + Bu_i$$

Goal

Design a **feedback controller** assigning u_i to drive the solutions to *synchronization* using information received only at *communication event times*.

Synchronization Over a Network

Let the dynamics of each node of the network be

$$\dot{z}_i = Az_i + Bu_i$$

Goal

Design a **feedback controller** assigning u_i to drive the solutions to *synchronization* using information received only at **communication event times**. Namely, ensure

- ▶ $\lim_{t \rightarrow \infty} |z_i(t) - z_k(t)| = 0$ for each $i, k \in \mathcal{V}$
- ▶ and Lyapunov stability of the set of points z such that

$$z_i = z_k \quad \forall i, k \in \mathcal{V}$$

Synchronization Over a Network

Let the dynamics of each node of the network be

$$\dot{z}_i = Az_i + Bu_i$$

Goal

Design a **feedback controller** assigning u_i to drive the solutions to *synchronization* using information received only at **communication event times**. Namely, ensure

- ▶ $\lim_{t \rightarrow \infty} |z_i(t) - z_k(t)| = 0$ for each $i, k \in \mathcal{V}$
- ▶ and Lyapunov stability of the set of points z such that

$$z_i = z_k \quad \forall i, k \in \mathcal{V}$$

Proposed Controller: Controller with state η_i assigns $u_i = \eta_i$

$$\begin{cases} \dot{\eta}_i(t) = 0 & \text{when } t \in \{t_\ell\}_{\ell=1}^{\infty} \\ \eta_i^+ = \frac{K_i}{d_i^{\text{in}}} \sum_{k \in \mathcal{J}_i} (z_i(t) - z_k(t)) & \text{when } t \notin \{t_\ell\}_{\ell=1}^{\infty} \end{cases}$$

where $\mathcal{J}_i = \{k : (i, k) \in \mathcal{E}\}$ collects i -agent neighbors and d_i^{in} is its in-degree.

Synchronization Over a Network

Let the dynamics of each node of the network be

$$\dot{z}_i = Az_i + Bu_i$$

Goal

Design a **feedback controller** assigning u_i to drive the solutions to *synchronization* using information received only at **communication event times**. Namely, ensure

- ▶ $\lim_{t \rightarrow \infty} |z_i(t) - z_k(t)| = 0$ for each $i, k \in \mathcal{V}$
- ▶ and Lyapunov stability of the set of points z such that

$$z_i = z_k \quad \forall i, k \in \mathcal{V}$$

Proposed Controller: Controller with state n assigns $u_i = n$.

Globally exponentially stabilize the set, denoted \mathcal{A}_{sync} ,
collecting all points such that

$$z_i = z_k$$

that is, render the “*diagonal in z* ” set GES

Outline

1. Introduction

- ▶ Motivation, Approach, and Recent Contributions
- ▶ Prevalent Network Control Applications

2. Hybrid Systems Tools for Control of Networks

- ▶ Hybrid Inclusion Models
- ▶ Lyapunov Stability Tools
- ▶ Robustness Tools
- ▶ Applications to Network Estimation and Synchronization

3. Conclusion

General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is


General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in \textcolor{blue}{f}(x, u) & (x, u) \in \textcolor{blue}{C} \\ x^+ & \in \textcolor{red}{g}(x, u) & (x, u) \in \textcolor{red}{D} \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is

- solutions starting close to \mathcal{A} stay close (*stability*)




General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is

- solutions starting close to \mathcal{A} stay close (*stability*)




General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is

- solutions starting close to \mathcal{A} stay close (*stability*)




General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is

- solutions starting close to \mathcal{A} stay close (*stability*)




General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is

- ▶ solutions starting close to \mathcal{A} stay close (*stability*)
- ▶ bounded solutions; complete ones approach \mathcal{A} (*attractivity*)




General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is

- ▶ solutions starting close to \mathcal{A} stay close (*stability*)
- ▶ bounded solutions; complete ones approach \mathcal{A} (*attractivity*)



General Control Problem

Given a set \mathcal{A} and a hybrid system \mathcal{H} to be controlled

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x, u) & (x, u) \in C \\ x^+ & \in g(x, u) & (x, u) \in D \\ y & = h(x, u) \end{array} \right.$$

design a **feedback law** so that \mathcal{A} is asymptotically stable, that is

- ▶ solutions starting close to \mathcal{A} stay close (*stability*)
- ▶ bounded solutions; complete ones approach \mathcal{A} (*attractivity*)

The **feedback law** could be

output feedback: use y instead of x

- ▶ *static*: $u = \kappa(x)$
- ▶ *dynamic*: u is a function of x and other controller states

resulting in a **hybrid closed-loop system** \mathcal{H} (without inputs)

$$\mathcal{H} \quad \left\{ \begin{array}{ll} \dot{x} & \in f(x) & x \in C \\ x^+ & \in g(x) & x \in D \end{array} \right.$$

Lyapunov Stability Theorem

Theorem (Lyapunov Theorem)

Given a hybrid system \mathcal{H} with state x (and no inputs)

$$\begin{array}{ll} \dot{x} & \in f(x) & x \in C \\ x^+ & \in g(x) & x \in D \end{array}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists $V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that

- ▶ V is continuous and positive definite with respect to \mathcal{A}
- ▶ V is continuously differentiable on an open set containing C
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle \leq 0$ $\forall x \in C, f' \in f(x)$
 $\Delta V = V(g') - V(x) \leq 0$ $\forall x \in D, g' \in g(x)$
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle < 0$ $\forall x \in C \setminus \mathcal{A}, f' \in f(x)$
 $\Delta V = V(g') - V(x) < 0$ $\forall x \in D \setminus \mathcal{A}, g' \in g(x)$

Lyapunov Stability Theorem

Theorem (Lyapunov Theorem)


Given a hybrid system \mathcal{H} with state

$$\begin{aligned}\dot{x} &\in f(x) \\ x^+ &\in g(x)\end{aligned}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists a

$V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that

- ▶ V is continuous and positive definite
- ▶ V is continuously differentiable on an open set containing C
 - $\dot{V} = \langle \nabla V(x), f' \rangle \leq 0 \quad \forall x \in C, \quad f' \in f(x)$
 - $\Delta V = V(g') - V(x) \leq 0 \quad \forall x \in D, \quad g' \in g(x)$
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle < 0$
 - $\Delta V = V(g') - V(x) < 0$
 - $\forall x \in C \setminus \mathcal{A}, \quad f' \in f(x)$
 - $\forall x \in D \setminus \mathcal{A}, \quad g' \in g(x)$



Lyapunov Stability Theorem

Theorem (Lyapunov Theorem)

Given a hybrid system \mathcal{H} with state

$$\begin{aligned}\dot{x} &\in f(x) \\ x^+ &\in g(x)\end{aligned}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists a

$V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that

- ▶ V is continuous and positive definite
- ▶ V is continuously differentiable on an open set containing C


$$\dot{V} = \langle \nabla V(x), f' \rangle \leq 0 \quad \forall x \in C, \quad f' \in f(x)$$

$$\Delta V = V(g') - V(x) \leq 0 \quad \forall x \in D, \quad g' \in g(x)$$
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle < 0$

$$\Delta V = V(g') - V(x) < 0$$

$$\forall x \in C \setminus \mathcal{A}, \quad f' \in f(x)$$

$$\forall x \in D \setminus \mathcal{A}, \quad g' \in g(x)$$



Lyapunov Stability Theorem

Theorem (Lyapunov Theorem)


Given a hybrid system \mathcal{H} with state

$$\begin{aligned}\dot{x} &\in f(x) \\ x^+ &\in g(x)\end{aligned}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists a function

$V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that

- ▶ V is continuous and positive definite
- ▶ V is continuously differentiable on an open set containing C
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle \leq 0$ $\forall x \in C, f' \in f(x)$
- ▶ $\Delta V = V(g') - V(x) \leq 0$ $\forall x \in D, g' \in g(x)$
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle < 0$ $\forall x \in C \setminus \mathcal{A}, f' \in f(x)$
- ▶ $\Delta V = V(g') - V(x) < 0$ $\forall x \in D \setminus \mathcal{A}, g' \in g(x)$



Lyapunov Stability Theorem

Theorem (Lyapunov Theorem)

Given a hybrid system \mathcal{H} with state

$$\begin{aligned}\dot{x} &\in f(x) \\ x^+ &\in g(x)\end{aligned}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists a

$V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that


- ▶ V is continuous and positive definite
- ▶ V is continuously differentiable on an open set containing C

$$\dot{V} = \langle \nabla V(x), f' \rangle \leq 0 \quad \forall x \in C, \quad f' \in f(x)$$

$$\Delta V = V(g') - V(x) \leq 0 \quad \forall x \in D, \quad g' \in g(x)$$
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle < 0$

$$\Delta V = V(g') - V(x) < 0 \quad \forall x \in C \setminus \mathcal{A}, \quad f' \in f(x)$$

$$\Delta V = V(g') - V(x) < 0 \quad \forall x \in D \setminus \mathcal{A}, \quad g' \in g(x)$$



Lyapunov Stability Theorem

Theorem (Lyapunov Theorem)

Given a hybrid system \mathcal{H} with sta

$$\begin{array}{lcl} \dot{x} & \in & f(x) \\ x^+ & \in & g(x) \end{array}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if

 $V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that

- ▶ V is continuous and positive
- ▶ V is continuously differentiable on an open set containing C

- $\dot{V} = \langle \nabla V(x), f' \rangle \leq 0$
 $\Delta V = V(g') - V(x) \leq 0$


- $\dot{V} = \langle \nabla V(x), f' \rangle < 0$
 $\Delta V = V(g') - V(x) < 0$

$$\forall x \in C, \quad f' \in f(x)$$

$$\forall x \in D, \quad g' \in g(x)$$

$$\forall x \in C \setminus \mathcal{A}, \quad f' \in f(x)$$

$$\forall x \in D \setminus \mathcal{A}, \quad g' \in g(x)$$



Lyapunov Stability Theorem

Theorem (Lyapunov Theorem)

Given a hybrid system \mathcal{H} with state

$$\begin{aligned}\dot{x} &\in f(x) \\ x^+ &\in g(x)\end{aligned}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists a

$V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that


- ▶ V is continuous and positive definite
- ▶ V is continuously differentiable on an open set containing C

$$\dot{V} = \langle \nabla V(x), f' \rangle \leq 0 \quad \forall x \in C, \quad f' \in f(x)$$

$$\Delta V = V(g') - V(x) \leq 0 \quad \forall x \in D, \quad g' \in g(x)$$
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle < 0$

$$\Delta V = V(g') - V(x) < 0 \quad \forall x \in C \setminus \mathcal{A}, \quad f' \in f(x)$$

$$\Delta V = V(g') - V(x) < 0 \quad \forall x \in D \setminus \mathcal{A}, \quad g' \in g(x)$$



Lyapunov Theorem Relaxed Flows

Corollary

Given a hybrid system \mathcal{H} with state x (and no inputs)

$$\begin{array}{ll} \dot{x} & \in f(x) & x \in C \\ x^+ & \in g(x) & x \in D \end{array}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists $V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that

- ▶ V is continuous and positive definite with respect to \mathcal{A}
- ▶ V is continuously differentiable on an open set containing C
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle \leq 0 \quad \forall x \in C, \quad f' \in f(x)$
 $\Delta V = V(g') - V(x) \leq 0 \quad \forall x \in D, \quad g' \in g(x)$

Lyapunov Theorem Relaxed Flows

Corollary

Given a hybrid system \mathcal{H} with state x (and no inputs)

$$\begin{array}{ll} \dot{x} & \in f(x) & x \in C \\ x^+ & \in g(x) & x \in D \end{array}$$

a closed set $\mathcal{A} \subset \mathbb{R}^n$ is **asymptotically stable** if there exists $V : \mathbb{R}^n \rightarrow \mathbb{R}$ such that

- ▶ V is continuous and positive definite with respect to \mathcal{A}
- ▶ V is continuously differentiable on an open set containing C
- ▶ $\dot{V} = \langle \nabla V(x), f' \rangle \leq 0$ $\forall x \in C, f' \in f(x)$
 $\Delta V = V(g') - V(x) \leq 0$ $\forall x \in D, g' \in g(x)$
- ▶ Every maximal solution has arbitrarily large number of jumps
 $\Delta V = V(g') - V(x) < 0$ $\forall x \in D \setminus \mathcal{A}, g' \in g(x)$

Estimation Over a Network – Modeling

Time-varying and (potentially) stochastic system can be modeled as an autonomous hybrid inclusion

Idea: To capture all possible event sequences $\{t_\ell\}_{\ell=1}^\infty$ while removing dependency on time and stochastic dynamics, define

- ▶ $\tau \in [0, T_2]$ as a timer that, when expires, generates the communication events from the i -th agent to the j -th agent
- ▶ $e = z_i - \hat{z}_k$ as the estimation error used for analysis

Then, with $x = (e, \tau)$, we have

$$\mathcal{H}_{obs}^{ik} \left\{ \begin{array}{l} \dot{e} = A_i e \\ \dot{\tau} = -1 \end{array} \right\} =: f(x) \quad (e, \tau) \in C$$
$$\left\{ \begin{array}{l} e^+ = (I - L_k M_i) e \\ \tau^+ \in [T_1, T_2] \end{array} \right\} =: g(x) \quad (e, \tau) \in D$$

with the flow set and the jump set defined as

$$C = \mathbb{R}^n \times [0, T_2], \quad D = \{(e, \tau) : \tau = 0\}$$

Estimation Over a Network – Stability

Theorem (Global Estimation with Limited Information)

Given two positive scalars T_1 and T_2 such that $T_1 < T_2$, if there exist $P = P^\top > 0$ and a matrix L_k such that

$$(I - L_k M_i)^\top \exp(A_i^\top v) P \exp(A_i v) (I - L_k M_i) - P < 0 \quad (\star)$$

for all $v \in [T_1, T_2]$, then the set

$$\mathcal{A}_{obs} = \{ (z_i, \hat{z}_k, \tau) : \hat{z}_k = z_i, \tau \in [0, T_2] \}$$

is globally exponentially stable.

Estimation Over a Network – Stability

Theorem (Global Estimation with Limited Information)

Given two positive scalars T_1 and T_2 such that $T_1 < T_2$, if there exist $P = P^\top > 0$ and a matrix L_k such that

$$(I - L_k M_i)^\top \exp(A_i^\top v) P \exp(A_i v) (I - L_k M_i) - P < 0 \quad (\star)$$

for all $v \in [T_1, T_2]$, then the set

$$\mathcal{A}_{obs} = \{(z_i, \hat{z}_k, \tau) : \hat{z}_k = z_i, \tau \in [0, T_2]\}$$

is globally exponentially stable.

Construction of V : with $x = (z_i, \hat{z}_k, \tau)$, define

$$V(x) = e^\top \exp(A_i^\top \tau) P \exp(A_i \tau) e$$

F. Ferrante, F. Gouaisbaut, S. and S. Tarbouriech "State Estimation of Linear Systems in the Presence of Sporadic Measurements." To appear in Automatica, 2016.

Estimation Over a Network – Stability

Proposition (LMI version of (\star))

Let T_1 and T_2 be two given positive scalars such that $T_1 < T_2$. If there exist $P = P^\top > 0$, a matrix J , and a matrix F such that for every $v \in [T_1, T_2]$

$$\begin{bmatrix} -(F + F^\top) & F - JM_i & \exp(A_i^\top v)P \\ \star & -P & 0 \\ \star & \star & -P \end{bmatrix} < 0$$

then the matrices P and $L_k = F^{-1}J$ satisfy (\star) .

Estimation Over a Network – Stability

Proposition (LMI version of (\star))

Let T_1 and T_2 be two given positive scalars such that $T_1 < T_2$. If there exist $P = P^\top > 0$, a matrix J , and a matrix F such that for every $v \in [T_1, T_2]$

$$\begin{bmatrix} -(F + F^\top) & F - JM_i & \exp(A_i^\top v)P \\ \star & -P & 0 \\ \star & \star & -P \end{bmatrix} < 0$$

then the matrices P and $L_k = F^{-1}J$ satisfy (\star) .

To reduce the check to finitely many LMIs, we over approximate $\exp(A_i v)$ by

$$\exp(A_i v) \in \text{co}\{F_1, F_2, \dots, F_\nu\}$$

over $[T_1, T_2]$, and then solve the ν LMIs with appropriate F .

Proof Sketch.

The proof is based on the use of the following Lyapunov function

$$V(x) = e^\top \exp(A_i^\top \tau) P \exp(A_i \tau) e$$

which satisfies

recall that $\mathcal{A}_{obs} = \{(z_i, \hat{z}_k, \tau) : \hat{z}_k = z_i, \tau \in [0, T_2]\}$

$$\alpha_1 |x|_{\mathcal{A}_{obs}}^2 \leq V(x) \leq \alpha_2 |x|_{\mathcal{A}_{obs}}^2 \quad \forall x \in C \cup D \cup g(D)$$

The key properties of V are

$$\langle \nabla V(x), f(x) \rangle = 0 \quad \forall x \in C$$

and, by (\star) , it follows that for some $\beta > 0$

$$V(g') - V(x) \leq -\beta e^\top e = -\beta |x|_{\mathcal{A}_{obs}}^2 \quad \forall x \in D, g' \in g(x)$$

Then, to apply the Lyapunov Theorem with relaxed flows, we note that, for each solution ϕ , $(t, j) \in \text{dom } \phi$ is such that $t \leq T_2(j+1)$, which is a persistently jumping property.

Estimation with Optimized MATI

i-th Agent dynamics:


$$A_i = \begin{bmatrix} 0.1 & 1 \\ -1 & 0.1 \end{bmatrix}$$
$$M_i = \begin{bmatrix} 1 & 0 \end{bmatrix}$$

k-th Observer gain:

$$L_k = \begin{bmatrix} 1 \\ 0.173 \end{bmatrix}$$

Communication parameters:

$$T_1 = 0.1, \quad T_2 = 2.03$$



Estimation with Optimized MATI

i-th Agent dynamics:


$$A_i = \begin{bmatrix} 0.1 & 1 \\ -1 & 0.1 \end{bmatrix}$$
$$M_i = \begin{bmatrix} 1 & 0 \end{bmatrix}$$

k-th Observer gain:

$$L_k = \begin{bmatrix} 1 \\ 0.173 \end{bmatrix}$$

Communication parameters:

$$T_1 = 0.1, \quad T_2 = 2.03$$



The maximum MATI (T_2) from the discrete-time observer in [Halimi et al., Springer 13], with integration in between events, is $T_2 = 1.54$. Our approach improves the MATI by 32%!

Estimation Over a Network w/Information Fusion

Let the dynamics of the i -th node of the network be

$$\dot{z}_i = A_i z_i, \quad y_i = M_i z_i$$

Estimation Over a Network w/Information Fusion

Let the dynamics of the i -th node of the network be

$$\dot{z}_i = A_i z_i, \quad y_i = M_i z_i$$

Goal

Design of an **observer** for z_i that runs at each of the other agents and measures y_i at **communication event times** $\{t_\ell^i\}_{\ell=1}^\infty$ satisfying

$$T_1^i \leq t_{\ell+1} - t_\ell \leq T_2^i$$

where

- ▶ T_1^i defines the fastest communication rate
- ▶ T_2^i represents the Maximum Allowable Transfer Time (MATI)

Related Work

Periodic sampling case

- ▶ Observer-protocol pair for LTI networked systems (single agent)
[Dacic and Nesic AUT 08]
- ▶ Discrete observer for LTI networked systems (common information arrival times)
[Park and Martins CDC 12]
- ▶ Continuous observer with discrete information (assume local observability)
[Dorfler ea. JSTSP 13]
- ▶ Continuous-time observer for a class of nonlinear systems (single agent)
[Ahmed-Ali ea. SCL 13]

Continuous-discrete observer

- ▶ Lipschitz continuous-time systems of small dimensions using reachable sets (periodic)
[Farza ea. TAC 14] [Dinh ea. TAC 15]
- ▶ Impulsive systems approach (periodic)
[Mazenc ea. SIAM 15]
- ▶ Hybrid systems approach (single-agent case)
[Ferrante ea. AUT 16]

Hybrid Distributed Observer

The i -th agent runs the following (local) observer:

$$\dot{\hat{z}}_i = A\hat{z}_i + \eta_i$$

where η_i is an *information fusion state*, evolves **continuously** and updates **impulsively** at communication events.

Hybrid Distributed Observer

The i -th agent runs the following (local) observer:

$$\dot{\hat{z}}_i = A\hat{z}_i + \eta_i$$

where η_i is an *information fusion state*, evolves **continuously** and updates **impulsively** at communication events.

Hybrid Information Fusion

$$\dot{\eta}_i = h_i \eta_i \quad \tau_i \in [0, T_2^i]$$

$$\eta_i^+ = K_{ii}y_i^e + \sum_{k \in \mathcal{J}_i} K_{ik}y_k^e + \gamma \sum_{k \in \mathcal{J}_i} (\hat{z}_i - \hat{z}_k) \quad \tau_i = 0$$

$$y_i^e = M_i \hat{z}_i - y_i, \quad y_i = M_i z_i + m_i \quad \text{measurements w/ noise}$$

Hybrid Distributed Observer

The i -th agent runs the following (local) observer:

$$\dot{\hat{z}}_i = A\hat{z}_i + \eta_i$$

where η_i is an *information fusion state*, evolves **continuously** and updates **impulsively** at communication events.

Hybrid Information Fusion

$$\dot{\eta}_i = h_i \eta_i \quad \tau_i \in [0, T_2^i]$$

$$\eta_i^+ = K_{ii}y_i^e + \sum_{k \in \mathcal{J}_i} K_{ik}y_k^e + \gamma \sum_{k \in \mathcal{J}_i} (\hat{z}_i - \hat{z}_k) \quad \tau_i = 0$$

$$y_i^e = M_i \hat{z}_i - y_i, \quad y_i = M_i z_i + m_i \quad \text{measurements w/ noise}$$

Goal

Guarantee **exponential convergence of $\hat{z}_i - z$ to zero** for each i , **robustly to general perturbations** and potentially without local detectability (at each node).

Compact Formulation and Error Dynamics

Denote the local estimation error $e_i = \hat{z}_i - z$, $e = (e_1, e_2, \dots, e_N)$ and $\eta = (\eta_1, \eta_2, \dots, \eta_N)$, it follows that

$$\left. \begin{aligned} \dot{e} &= (I_N \otimes A)e + \eta \\ \dot{\eta} &= H(h)\eta \end{aligned} \right\} \text{ when } \tau_i \in [0, T_2^i] \quad \forall i \in \mathcal{V}$$

while when $\tau_i = 0$ for some $i \in \mathcal{V}$,

$$\begin{aligned} e^+ &= e \\ \eta_i^+ &= K_{ii}y_i^e + \sum_{k \in \mathcal{V}} g_{ik} K_{ik}y_k^e + \gamma \sum_{k \in \mathcal{V}} g_{ik}(\hat{z}_i - \hat{z}_k) \end{aligned}$$

- ▶ $H(h) = \text{diag}(h_1, h_2, \dots, h_N)$
- ▶ K_{ii} , K_{ik} 's are gains for output errors
- ▶ $\gamma \in \mathbb{R}$ is a constant gain for consensus

Compact Formulation and Error Dynamics

Denote the local estimation error $e_i = \hat{z}_i - z$, $e = (e_1, e_2, \dots, e_N)$ and $\eta = (\eta_1, \eta_2, \dots, \eta_N)$, it follows that

$$\left. \begin{aligned} \dot{e} &= (I_N \otimes A)e + \eta \\ \dot{\eta} &= H(h)\eta \end{aligned} \right\} \text{ when } \tau_i \in [0, T_2^i] \quad \forall i \in \mathcal{V}$$

while when $\tau_i = 0$ for some $i \in \mathcal{V}$,

$$e^+ = e$$

$$\eta_i^+ = K_{ii}y_i^e + \sum_{k \in \mathcal{V}} g_{ik} K_{ik} y_k^e + \gamma \sum_{k \in \mathcal{V}} g_{ik} (\hat{z}_i - \hat{z}_k)$$

Catch: Complex behavior at communication events

- ▶ Which τ_i is zero?
- ▶ How many τ_i 's are zero?
- ▶ What is a Lyapunov function candidate?

Compact Formulation and Error Dynamics

Idea: Define the new coordinates

$$\theta_i = K_{ii}y_i^e + \sum_{k \in \mathcal{J}_i} K_{ik}y_k^e + \gamma \sum_{k \in \mathcal{J}_i} (e_i - e_k) - \eta_i$$

Compact Formulation and Error Dynamics

Idea: Define the new coordinates

$$\theta_i = K_{ii}y_i^e + \sum_{k \in \mathcal{J}_i} K_{ik}y_k^e + \gamma \sum_{k \in \mathcal{J}_i} (e_i - e_k) - \eta_i$$

Denoting $e = (e_1, \dots, e_N)$, $\theta = (\theta_1, \dots, \theta_N)$, $\tau = (\tau_1, \dots, \tau_N)$

- ▶ $\theta = ((K_g M_g) * (I_N + \mathcal{G}) + \gamma \mathcal{L} \otimes I_n)e - \eta$
- ▶ K_g is a $N \times N$ block matrix with the (i, k) -th entry given by $K_{ik} \in \mathbb{R}^{n \times p}$ for all $i, k \in \mathcal{V}$
- ▶ M_g is block diagonal, $M_g = \text{diag}(M_1, M_2, \dots, M_N)$
- ▶ the operation “ $*$ ” denotes the Khatri-Rao product, where the matrix $K_g M_g$ is treated as a $N \times N$ block matrix

Y. Li, S. Phillips, and S, "On Distributed Observers for Linear Time-invariant Systems Under Intermittent Information Constraints", *Proceedings of 10th IFAC Symposium on Nonlinear Control Systems (NOLCOS)*, 2016.

Compact Formulation and Error Dynamics

Idea: Define the new coordinates

$$\theta_i = K_{ii}y_i^e + \sum_{k \in \mathcal{J}_i} K_{ik}y_k^e + \gamma \sum_{k \in \mathcal{J}_i} (e_i - e_k) - \eta_i$$

$$\begin{aligned}\dot{e} &= \underbrace{(I_N \otimes A + \mathcal{K})}_{A_\theta} e - \theta \\ \dot{\theta} &= \mathcal{K} A_\theta e - \mathcal{K} \theta\end{aligned}$$

when $\tau \in \mathcal{T}$, $\mathcal{K} = K_g M_g * (I_N + \mathcal{G}) + \gamma \mathcal{L} \otimes I_n$, and

$$\begin{aligned}e_i^+ &= e_i \\ \theta_i^+ &= 0\end{aligned}$$

when $\tau_i = 0$ for some i , $\mathcal{T} := [0, T_2^1] \times [0, T_2^2] \times \cdots \times [0, T_2^N]$

Compact Formulation and Error Dynamics

Interconnection as a Hybrid System

The interconnection \mathcal{H} has state $\chi = (\sigma, \tau)$, $\sigma = (e, \theta)$, with data

$$f(\chi) := (A_{f\theta}\sigma, -\mathbf{1}_N), \quad A_{f\theta} = \begin{bmatrix} A_\theta & -I_{nN} \\ \mathcal{K}A_\theta & -\mathcal{K} \end{bmatrix}$$

for each $\chi \in C = \mathcal{X} := \mathbb{R}^{2nN} \times \mathcal{T}$,

$$g(\chi) := \{g_i(\chi) : \chi \in D_i, i \in \mathcal{V}\}$$

when $\chi \in D = \bigcup_{i \in \mathcal{V}} D_i$, $D_i = \{\chi \in C : \tau_i = 0\}$,

$$g_i(\chi) = \begin{bmatrix} e \\ (\theta_1, \theta_2, \dots, \theta_{i-1}, 0, \theta_{i+1}, \dots, \theta_N) \\ (\tau_1, \tau_2, \dots, \tau_{i-1}, [T_1^i, T_2^i], \tau_{i+1}, \dots, \tau_N) \end{bmatrix}$$

Sufficient Conditions for GES

Global Exponential Stability of Zero Estimation Error

Let $0 < T_1^i \leq T_2^i$ be given. Suppose N agents are connected via a digraph $\Gamma = (\mathcal{V}, \mathcal{E}, \mathcal{G})$. Moreover, suppose there exist $\gamma \in \mathbb{R}$, $\delta > 0$ and matrices $K_g \in \mathbb{R}^{nN \times p}$, $P \in \mathbb{R}^{nN \times nN}$, $Q_i \in \mathbb{R}^{n \times N}$ satisfying $P = P^\top > 0$, $Q_i = Q_i^\top > 0$ for all $i \in \mathcal{V}$, and

$$\mathcal{N} := \begin{bmatrix} \text{He}(A_\theta, P) & -P + \tilde{A}_\theta^\top \mathcal{K}^\top \tilde{Q}(\nu) \\ \star & -\delta \tilde{Q}(\nu) - \text{He}(\tilde{\mathcal{K}}, \tilde{Q}(\nu)) \end{bmatrix} < 0$$

$$\forall \nu = (\nu_1, \nu_2, \dots, \nu_N) \in \mathcal{T}$$

with

$$\tilde{Q}(\nu) = \text{diag}(\exp(\delta \nu_1) Q_1, \dots, \exp(\delta \nu_N) Q_N).$$

Then, the set $\mathcal{A} = \{0_{nN}\} \times \{0_{nN}\} \times \mathcal{T}$ is **GES for the hybrid system \mathcal{H}** .

Lyapunov-based Analysis

Proof sketch: Consider the Lyapunov function candidate

$$V(x) = e^\top P e + \theta^\top \tilde{Q}(\tau) \theta \quad \forall x \in \mathcal{X}$$

with the data of \mathcal{H} . It can be shown that

- ▶ $\langle \nabla V(x), f(x) \rangle \leq -|\bar{\lambda}(\mathcal{N})| |x|_{\mathcal{A}}^2$ for each $x \in C$,
- ▶ $V(g') - V(x) \leq 0$ for each $x \in D$ and for each $g' \in g(x)$

which using a Lyapunov Theorem with relaxed jumps leads us to



$$|\phi(t, j)|_{\mathcal{A}} \leq \sqrt{\frac{\alpha_2}{\alpha_1}} \exp \left(-\frac{|\bar{\lambda}(\mathcal{N})|}{2\alpha_2} \min \left\{ \epsilon, (1 - \epsilon) \frac{T_1^{\min}}{2N} \right\} (t + j) \right) |\phi(0, 0)|_{\mathcal{A}}$$

where $\epsilon \in (0, 1)$,

$$\alpha_1 = \min \left\{ \underline{\lambda}(P), \underline{\lambda}(\tilde{Q}(0)) \right\}, \quad \alpha_2 = \max \left\{ \bar{\lambda}(P), \bar{\lambda}(\tilde{Q}(\bar{T}_2)) \right\},$$

and $\bar{T}_2 = (T_2^1, T_2^2, \dots, T_2^N)$, $\bar{\lambda}$ gives the maximum eigenvalue, $\underline{\lambda}$ gives the minimum, and T_1^{\min} is the minimum over the T_1^i 's

Estimation without Local Detectability



Plant Dynamics:

$$A = \begin{bmatrix} 0 & -1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$



$$M_1 = \begin{bmatrix} 0 & 0 & 1 \end{bmatrix}$$

$$M_2 = \begin{bmatrix} 1 & 1 & 0 \end{bmatrix}$$

Communication Parameters:

$$T_1^i = 0.2, \quad T_2^i = 0.4$$

Estimation without Local Detectability



Plant Dynamics:

$$A = \begin{bmatrix} 0 & -1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

$$M_1 = \begin{bmatrix} 0 & 0 & 1 \end{bmatrix}$$

$$M_2 = \begin{bmatrix} 1 & 1 & 0 \end{bmatrix}$$

Communication Parameters:

$$T_1^i = 0.2, \quad T_2^i = 0.4$$

Without communication,
no agent can estimate x

Synchronization Over a Network – Modeling

As for the estimation problem, we use a timer

- ▶ τ as a timer that, when expires, generates the communication events between the agents

Synchronization Over a Network – Modeling

As for the estimation problem, we use a timer

- ▶ τ as a timer that, when expires, generates the communication events between the agents

with dynamics

$$\begin{cases} \dot{\tau} = -1 & \tau \in [0, T_2] \\ \tau^+ \in [T_1, T_2] & \tau = 0 \end{cases}$$

Synchronization Over a Network – Modeling

As for the estimation problem, we use a timer

- ▶ τ as a timer that, when expires, generates the communication events between the agents

- ▶ and the local average error $e_i = \frac{1}{d_i^{in}} \sum_{k \in \mathcal{J}_i} (z_i - z_k)$

Synchronization Over a Network – Modeling

As for the estimation problem, we use a timer

- τ as a timer that, when expires, generates the communication events between the agents

Then, with $x = (\chi, \tau)$, $\chi = (\chi_1, \chi_2, \dots, \chi_N)$, $\chi_i = (e_i, \eta_i)$, we have

$$\mathcal{H}_{sync} : \begin{cases} \dot{x} = \begin{bmatrix} \bar{A}_f \chi \\ -1 \end{bmatrix} =: f(x) & x \in C = \mathbb{R}^{N(n+p)} \times [0, T_2] \\ x^+ \in \begin{bmatrix} \bar{A}_g \chi \\ [T_1, T_2] \end{bmatrix} =: g(x) & x \in D = \mathbb{R}^{N(n+p)} \times \{0\} \end{cases}$$

where

$$\bar{A}_f = I_N \otimes A_f - (\mathcal{G}^\top \mathcal{J}^{-1}) \otimes B_f \quad \bar{A}_g = \text{diag}(A_{g1}, A_{g2}, \dots, A_{gN})$$

$$A_f = \begin{bmatrix} A & B \\ 0 & 0 \end{bmatrix}, \quad B_f = \begin{bmatrix} 0 & B \\ 0 & 0 \end{bmatrix}, \quad A_{gi} = \begin{bmatrix} I & 0 \\ K_i & 0 \end{bmatrix}$$

Synchronization over Networks – Stability

Theorem (Global Synchronization with Intermittent Information)

Given two positive scalars T_1 and T_2 such that $T_1 \leq T_2$ and the digraph Γ , then the set

$$\tilde{\mathcal{A}}_{sync} = \{(\chi, \tau) : \chi = 0, \tau \in [0, T_2] \}$$

is **globally exponentially stable** when

Synchronization over Networks – Stability

Theorem (Global Synchronization with Intermittent Information)

Given two positive scalars T_1 and T_2 such that $T_1 \leq T_2$ and the digraph Γ , then the set

$$\tilde{\mathcal{A}}_{sync} = \{(\chi, \tau) : \chi = 0, \tau \in [0, T_2] \}$$

is **globally exponentially stable** when

- ▶ the graph Γ is strongly connected and there exist $\sigma > 0$, $P = P^\top > 0$, and, for each $i \in \mathcal{V}$, a matrix K_i such that

$$\exp(\sigma v) \bar{A}_g^\top \exp(\bar{A}_f^\top v) P \exp(\bar{A}_f v) \bar{A}_g - P < 0 \quad (**)$$

Synchronization over Networks – Stability

Theorem (Global Synchronization with Intermittent Information)

Given two positive scalars T_1 and T_2 such that $T_1 \leq T_2$ and the digraph Γ , then the set

$$\tilde{\mathcal{A}}_{sync} = \{(\chi, \tau) : \chi = 0, \tau \in [0, T_2] \}$$

is **globally exponentially stable** when

- ▶ the graph Γ is strongly connected and there exist $\sigma > 0$, $P = P^\top > 0$, and, for each $i \in \mathcal{V}$, a matrix K_i such that

$$\exp(\sigma v) \bar{A}_g^\top \exp(\bar{A}_f^\top v) P \exp(\bar{A}_f v) \bar{A}_g - P < 0 \quad (**)$$

- ▶ the graph Γ is completely connected and there exist $\sigma > 0$, $P = P^\top > 0$, and a matrix K such that

$$\exp(\sigma v) A_g^\top \exp(A_f^\top v) P \exp(A_f v) A_g - P < 0 \quad (***)$$

for each $v \in [T_1, T_2]$.

Synchronization over Networks – Stability

Theorem (Global Synchronization with Intermittent Information)

Given two positive scalars T_1 and T_2 such that $T_1 \leq T_2$ and the digraph Γ , then the set

$$\tilde{\mathcal{A}}_{sync} = \{(\chi, \tau) : \chi = 0, \tau \in [0, T_2] \}$$

is **globally exponentially stable** when

- ▶ the graph Γ is strongly connected and there exist $\sigma > 0$, $P = P^\top > 0$ and for each $i \in \mathcal{N}$ a matrix K_i such that


Construction of V (for strongly connected case):

with $x = (\chi, \tau)$ and $\sigma > 0$, define

$$V(x) = \exp(\sigma\tau)\chi^\top \exp(\bar{A}_f^\top \tau)P \exp(\bar{A}_f \tau)\chi$$

S. Phillips, and S. "Robust Synchronization of Interconnected Linear Systems over Intermittent Communication Networks", In Proceedings of the American Control Conference (ACC), 2016.

Synchronization Over a Network - Simulation



i -th **Agent Dynamics:**

$$A = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$$

$$B = \begin{bmatrix} 0 & 1 \end{bmatrix}$$


i -th **Controller Gain:**

$$K_i = - \begin{bmatrix} 0.5 & 0.7 \end{bmatrix}$$

Communication Parameters:

$$T_1 = 0.3, \quad T_2 = 0.65$$

Synchronization Over a Network - Simulation



i -th Agent Dynamics:

$$A = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$$

$$B = \begin{bmatrix} 0 & 1 \end{bmatrix}$$

eters:

Local Distributed Hybrid Controller, η_i

The i -th agent assigns its input to the following local controller state:

$$u_i = \eta_i$$

where the dynamics of η_i is given by a zero-order hybrid protocol that updates impulsively at communication events.

Local Distributed Hybrid Controller, η_i

The i -th agent assigns its input to the following local controller state:

$$u_i = \eta_i$$

where the dynamics of η_i is given by a zero-order hybrid protocol that updates impulsively at communication events.

Controller Algorithm

$$\dot{\eta}_i = 0$$

$$\tau \in [0, T_2]$$

$$\eta_i^+ = -\gamma \sum_{k=1}^N g_{ik}(x_i - x_k) \quad \tau = 0$$

where g_{ik} are the components of the adjacency matrix.

Local Distributed Hybrid Controller, η_i

The i -th agent assigns its input to the following local controller state:

$$u_i = \eta_i$$

where the dynamics of η_i is given by a zero-order hybrid protocol that updates impulsively at communication events.

Controller Algorithm

$$\dot{\eta}_i = 0$$

$$\tau \in [0, T_2]$$

$$\eta_i^+ = -\gamma \sum_{k=1}^N g_{ik}(x_i - x_k) \quad \tau = 0$$

where g_{ik} are the components of the adjacency matrix.

Goal

Guarantee **pointwise exponential stability** of the set of points $x_i = x_k$ for each i, k with robustness to communication noise.

Local Distributed Hybrid Controller, η_i

The i -th agent assigns its input to the following local controller state:

$$u_i = \eta_i$$

where the dynamics of η_i is given by a zero-order hybrid protocol that updates impulsively at communication events.

Controller Algorithm

$$\dot{\eta}_i = 0 \quad \tau \in [0, T_2]$$

$$\eta_i^+ = -\gamma \sum_{k=1}^N g_{ik}(x_i - x_k) \quad \tau = 0$$

where g_{ik} are the components of the adjacency matrix.

Goal

S. Phillips, Y. Li, and S. "On Distributed Intermittent Consensus for First-Order Systems with Robustness." In Proceedings of 10th IFAC Symposium on Nonlinear Control Systems (NOLCOS), 2016.

Partial Pointwise Global Exponential Stability

Definition

Consider a hybrid system \mathcal{H} with state $x = (p, q) \in \mathbb{R}^n$. The closed set $\mathcal{A} \subset \mathbb{R}^r \times \mathbb{R}^{n-r}$ where $r \in \mathbb{N}$ and $0 < r \leq n$ is **partially pointwise globally exponentially stable** with respect to the state component p if

1. \mathcal{A} is exponentially attractive
2. every maximal solution ϕ to \mathcal{H} is complete and has a limit belonging to \mathcal{A}
3. for each $p^* \in \mathbb{R}^r$ s.t. there exists $q \in \mathbb{R}^{n-r}$ satisfying $(p^*, q) \in \mathcal{A}$, it follows that for each $\varepsilon > 0$ there exists $\delta > 0$ such that every solution ϕ to \mathcal{H} is such that its p component ϕ_p satisfies

$$|\phi_p(0, 0) - p^*| \leq \delta \implies |\phi_p(t, j) - p^*| \leq \varepsilon$$

for all $(t, j) \in \text{dom } \phi$.

Partial Pointwise Global Exponential Stability

Definition

Consider a hybrid system \mathcal{H} with state $x = (p, q) \in \mathbb{R}^n$. The closed set $\mathcal{A} \subset \mathbb{R}^r \times \mathbb{R}^{n-r}$ where $r \in \mathbb{N}$ and $0 < r \leq n$ is **partially pointwise globally exponentially stable** with respect to the state component p if

1. \mathcal{A} is exponentially attractive
2. every maximal solution ϕ to \mathcal{H} is complete and has a limit belonging to \mathcal{A}
3. for each $p^* \in \mathbb{R}^r$ s.t. there exists $q \in \mathbb{R}^{n-r}$ satisfying $(p^*, q) \in \mathcal{A}$, it follows that for each $\varepsilon > 0$ there exists $\delta > 0$ such that every solution ϕ to \mathcal{H} is such that its p component ϕ_p satisfies

$$|\phi_p(0, 0) - p^*| \leq \delta \implies |\phi_p(t, j) - p^*| \leq \varepsilon$$

for all $(t, j) \in \text{dom } \phi$.

Partial Pointwise Global Exponential Stability

Definition

Consider a hybrid system \mathcal{H} with state $x = (p, q) \in \mathbb{R}^n$. The closed set $\mathcal{A} \subset \mathbb{R}^r \times \mathbb{R}^{n-r}$ where $r \in \mathbb{N}$ and $0 < r \leq n$ is **partially pointwise globally exponentially stable** with respect to the state component p if

1. \mathcal{A} is exponentially attractive
2. every maximal solution ϕ to \mathcal{H} is complete and has a limit belonging to \mathcal{A}
3. for each $p^* \in \mathbb{R}^r$ s.t. there exists $q \in \mathbb{R}^{n-r}$ satisfying $(p^*, q) \in \mathcal{A}$, it follows that for each $\varepsilon > 0$ there exists $\delta > 0$ such that every solution ϕ to \mathcal{H} is such that its p component ϕ_p satisfies

$$|\phi_p(0, 0) - p^*| \leq \delta \implies |\phi_p(t, j) - p^*| \leq \varepsilon$$

for all $(t, j) \in \text{dom } \phi$.

Partial Pointwise Global Exponential Stability

Definition

Consider a hybrid system \mathcal{H} with state $x = (p, q) \in \mathbb{R}^n$. The closed set $\mathcal{A} \subset \mathbb{R}^r \times \mathbb{R}^{n-r}$ where $r \in \mathbb{N}$ and $0 < r \leq n$ is **partially pointwise globally exponentially stable** with respect to the state component p if

1. \mathcal{A} is exponentially attractive
2. every maximal solution ϕ to \mathcal{H} is complete and has a limit belonging to \mathcal{A}
3. for each $p^* \in \mathbb{R}^r$ s.t. there exists $q \in \mathbb{R}^{n-r}$ satisfying $(p^*, q) \in \mathcal{A}$, it follows that for each $\varepsilon > 0$ there exists $\delta > 0$ such that every solution ϕ to \mathcal{H} is such that its p component ϕ_p satisfies

$$|\phi_p(0, 0) - p^*| \leq \delta \implies |\phi_p(t, j) - p^*| \leq \varepsilon$$

for all $(t, j) \in \text{dom } \phi$.

Stability Results

Main Results

Let $0 < T_1 \leq T_2$, and Γ be **strongly connected** and **weight balanced**. If there exists a positive scalar γ and $P = P^\top > 0$ such that

$$A_g^\top e^{A_f^\top \nu} P e^{A_f \nu} A_g - P < 0$$
$$A_f = \begin{bmatrix} 0 & I \\ 0 & 0 \end{bmatrix}$$
$$A_g = \begin{bmatrix} I & 0 \\ -\gamma \bar{\mathcal{L}} & 0 \end{bmatrix}$$

for each $\nu \in [T_1, T_2]$ where $\bar{\mathcal{L}} = \text{diag}(\lambda(\mathcal{L}) \setminus \{0\})$, then

- the hybrid system \mathcal{H}_{sync} has the set \mathcal{A}_{sync} **GES**.

Stability Results

Main Results

Let $0 < T_1 \leq T_2$, and Γ be **strongly connected** and **weight balanced**. If there exists a positive scalar γ and $P = P^\top > 0$ such that

$$A_g^\top e^{A_f^\top \nu} P e^{A_f \nu} A_g - P < 0$$
$$A_f = \begin{bmatrix} 0 & I \\ 0 & 0 \end{bmatrix}$$
$$A_g = \begin{bmatrix} I & 0 \\ -\gamma \bar{\mathcal{L}} & 0 \end{bmatrix}$$

for each $\nu \in [T_1, T_2]$ where $\bar{\mathcal{L}} = \text{diag}(\lambda(\mathcal{L}) \setminus \{0\})$, then

- the hybrid system \mathcal{H}_{sync} has the set \mathcal{A}_{sync} **GES**.

Stability Results

Main Results

Let $0 < T_1 \leq T_2$, and Γ be **strongly connected** and **weight balanced**. If there exists a positive scalar γ and $P = P^\top > 0$ such that

$$A_g^\top e^{A_f^\top \nu} P e^{A_f \nu} A_g - P < 0$$
$$A_f = \begin{bmatrix} 0 & I \\ 0 & 0 \end{bmatrix}$$
$$A_g = \begin{bmatrix} I & 0 \\ -\gamma \bar{\mathcal{L}} & 0 \end{bmatrix}$$

for each $\nu \in [T_1, T_2]$ where $\bar{\mathcal{L}} = \text{diag}(\lambda(\mathcal{L}) \setminus \{0\})$, then

- ▶ the hybrid system \mathcal{H}_{sync} has the set \mathcal{A}_{sync} **GES**.
- ▶ every solution ϕ is **complete** and

$$\lim_{t+j \rightarrow \infty} z_i(t, j) = \frac{1}{N} \sum_{i=1}^N z_i(0, 0) + \eta_i(0, 0) \tau(0, 0)$$

Stability Results

Main Results

Let $0 < T_1 \leq T_2$, and Γ be **strongly connected** and **weight balanced**. If there exists a positive scalar γ and $P = P^\top > 0$ such that

$$A_g^\top e^{A_f^\top \nu} P e^{A_f \nu} A_g - P < 0$$
$$A_f = \begin{bmatrix} 0 & I \\ 0 & 0 \end{bmatrix}$$
$$A_g = \begin{bmatrix} I & 0 \\ -\gamma \bar{\mathcal{L}} & 0 \end{bmatrix}$$

for each $\nu \in [T_1, T_2]$ where $\bar{\mathcal{L}} = \text{diag}(\lambda(\mathcal{L}) \setminus \{0\})$, then

- ▶ the hybrid system \mathcal{H}_{sync} has the set \mathcal{A}_{sync} **GES**.
- ▶ every solution ϕ is **complete** and

$$\lim_{t+j \rightarrow \infty} z_i(t, j) = \frac{1}{N} \sum_{i=1}^N z_i(0, 0) + \eta_i(0, 0) \tau(0, 0)$$

- ▶ the set \mathcal{A} is **partially pointwise globally exponentially stable** with respect to (z, η) for the hybrid system \mathcal{H}_{sync} .

Proof Sketch.

Let $x = (\chi, \tau)$, $\chi = (e, \eta)$ and $e_i = z_i - \sum_{k=1}^N z_i$. The proof is based off the following Lyapunov function

$$V(x) = \chi^\top \tilde{T} \exp(A_{f2}^\top \tau) P \exp(A_{f2} \tau) \tilde{T}^\top \chi$$

where $\tilde{T} = \text{diag}(T, T)$ and T is an orthonormal diagonalizing matrix for the Laplacian \mathcal{L} .

Proof Sketch.

Let $x = (\chi, \tau)$, $\chi = (e, \eta)$ and $e_i = z_i - \sum_{k=1}^N z_i$. The proof is based off the following Lyapunov function

$$V(x) = \chi^\top \tilde{T} \exp(A_{f_2}^\top \tau) P \exp(A_{f_2} \tau) \tilde{T}^\top \chi$$

where $\tilde{T} = \text{diag}(T, T)$ and T is an orthonormal diagonalizing matrix for the Laplacian \mathcal{L} . Moreover, V satisfies

$$\alpha_1 |x|_{\tilde{\mathcal{A}}_{sync}}^2 \leq V(x) \leq \alpha_2 |x|_{\tilde{\mathcal{A}}_{sync}}^2$$

Then, the key properties of V are

- ▶ $\langle \nabla V(x), f(x) \rangle = 0$ for each $x \in C$,
- ▶ $V(g) - V(x) \leq -\beta |x|_{\tilde{\mathcal{A}}_{sync}}^2$ for each $x \in D$.

Proof Sketch.

Let $x = (\chi, \tau)$, $\chi = (e, \eta)$ and $e_i = z_i - \sum_{k=1}^N z_i$. The proof is based off the following Lyapunov function

$$V(x) = \chi^\top \tilde{T} \exp(A_{f_2}^\top \tau) P \exp(A_{f_2} \tau) \tilde{T}^\top \chi$$

where $\tilde{T} = \text{diag}(T, T)$ and T is an orthonormal diagonalizing matrix for the Laplacian \mathcal{L} . Moreover, V satisfies

$$\alpha_1 |x|_{\tilde{\mathcal{A}}_{sync}}^2 \leq V(x) \leq \alpha_2 |x|_{\tilde{\mathcal{A}}_{sync}}^2$$

Then, the key properties of V are

- ▶ $\langle \nabla V(x), f(x) \rangle = 0$ for each $x \in C$,
- ▶ $V(g) - V(x) \leq -\beta |x|_{\tilde{\mathcal{A}}_{sync}}^2$ for each $x \in D$.

which leads us to

$$|\phi(t, j)|_{\tilde{\mathcal{A}}_{sync}} \leq \exp\left(\frac{R}{2}\right) \sqrt{\frac{\alpha_2}{\alpha_1}} \exp\left(-\frac{\alpha}{2}(t + j)\right) |\phi(0, 0)|_{\tilde{\mathcal{A}}_{sync}}$$

where $\alpha \in \left(0, \frac{|\beta|}{1+T_2}\right)$, $R = \left[\frac{T_2|\beta|}{1+T_2}, \infty\right)$

Asynchronous Update Times

A local timer for each agent triggering communication

$$\begin{array}{ll} \dot{\tau}_i = -1 & \tau_i \in [0, T_2], \\ \tau_i^+ \in [T_1, T_2] & \tau_i = 0. \end{array}$$

when τ_i expires, information is transferred to agent i .

Asynchronous Update Times

A local timer for each agent triggering communication

$$\begin{aligned}\dot{\tau}_i &= -1 & \tau_i &\in [0, T_2], \\ \tau_i^+ &\in [T_1, T_2] & \tau_i &= 0.\end{aligned}$$

when τ_i expires, information is transferred to agent i .

Consensus Algorithm

$$\begin{aligned}\dot{\eta}_i &= h\eta_i & \tau_i &\in [0, T_2] \\ \eta_i^+ &= -\gamma \sum_{k=1}^N g_{ik}(z_i - z_k) & \tau_i &= 0\end{aligned}$$

where g_{ik} are the components of the adjacency matrix.

- the gains h and γ are to be determined.

Asynchronous Update Times

A local timer for each agent triggering communication

$$\begin{aligned}\dot{\tau}_i &= -1 & \tau_i &\in [0, T_2], \\ \tau_i^+ &\in [T_1, T_2] & \tau_i &= 0.\end{aligned}$$

when τ_i expires, information is transferred to agent i .


Consensus Algorithm

$$\dot{\eta}_i = h\eta_i \quad \tau_i \in [0, T_2]$$

$$\eta_i^+ = -\gamma \sum_{k=1}^N g_{ik}(z_i - z_k) \quad \tau_i = 0$$

where g_{ik}

► the



Synchronization Over a Network

Hybrid System, \mathcal{H} , with asynchronous update times

\mathcal{H}_{sync} has state $x = (z, \eta, \tau) \in \mathcal{X} := \mathbb{R}^{2N} \times [0, T_2]^N$ with the following dynamics

$$\dot{x} := \begin{bmatrix} \eta \\ h\eta \\ -1_N \end{bmatrix} \quad \forall x \in \mathcal{X}$$

jumps are induced when a single timer state reaches 0, i.e. when $x \in \bigcup_{i \in \mathcal{V}} D_i$, $D_i = \{x \in \mathcal{X} : \tau_i = 0\}$. Then,

$$x^+ \in \{G_i(x) : x \in D_i, i \in \mathcal{V}\}$$

where

$$G_i(x) = \begin{bmatrix} z \\ (\eta_1, \eta_2, \dots, \eta_{i-1}, -\gamma \sum_{k=1}^N g_{ik}(z_i - z_k), \eta_{i+1}, \dots, \eta_N) \\ (\tau_1, \tau_2, \dots, \tau_{i-1}, [T_1, T_2], \tau_{i+1}, \dots, \tau_N) \end{bmatrix}$$

Asynchronous Update Times - Stability

Proposition

Given $0 < T_1 \leq T_2$ and a **strongly connected** and **weight balanced** digraph Γ . If there exist scalars $\gamma, h \in \mathbb{R}$, and $\sigma > 0$, positive definite diagonal matrices P and Q such that

$$\begin{bmatrix} \gamma \text{He}(P, \mathcal{L}) & -P\Pi + \mathcal{K}_1^\top QE(\tau) \\ \star & -\sigma QE(\tau) - \text{He}(QE(\tau), \mathcal{K}_2) \end{bmatrix} \leq 0 \quad (3)$$

for each $\tau \in [0, T_2]^N$, where $\Pi = I - \frac{1}{N} \mathbf{1}_N \mathbf{1}_N^\top$, $\mathcal{K}_1 = \gamma \mathcal{K}_2 \mathcal{L}$, $\mathcal{K}_2 = \gamma \mathcal{L} - hI$, and $E(\tau) = \text{diag}(e^{\sigma\tau_1}, e^{\sigma\tau_2}, \dots, e^{\sigma\tau_N})$, then the set \mathcal{A} is **globally asymptotically stable** for the hybrid system $\mathcal{H}_{\text{sync}}$.

Proof Sketch.

Let $x = (e, \theta, \tau)$, where $e_i = z_i - \sum_{k=1}^N z_k$ and $\theta_i = \gamma \sum_{k \in \mathcal{J}_i} (x_i - x_k) - \eta$. Consider the Lyapunov function candidate

$$V(x) = e^\top P e + \theta^\top Q E(\tau) \theta \quad \forall x \in \mathcal{X}$$

which satisfies

$$\alpha_1 |x|_{\mathcal{A}_{sync}}^2 \leq V(x) \leq \alpha_2 |x|_{\mathcal{A}_{sync}}^2$$

with the data of \mathcal{H} . As a consequence of (4), it can be shown that

- ▶ $\langle \nabla V(x), f(x) \rangle \leq 0$ for each $x \in C$
- ▶ $V(g') - V(x) \leq 0$ for each $x \in D$ and $g' \in g(x)$

Then, we apply the **Invariance Principle** involving a nonincreasing function, which results in global asymptotic stability of $\tilde{\mathcal{A}}_{sync}$.

Outline

1. Introduction

- ▶ Motivation, Approach, and Recent Contributions
- ▶ Prevalent Network Control Applications

2. Hybrid Systems Tools for Control of Networks

- ▶ Hybrid Inclusion Models
- ▶ Lyapunov Stability Tools
- ▶ Robustness Tools
- ▶ Applications to Network Estimation and Synchronization

3. Conclusion

Nominal Robustness For Networked Systems

Further results on robustness to

$$\rho > 0$$

► Parameter uncertainty

► Skewed clocks

$$\dot{\tau}_i = -1 \quad \rightarrow \quad \dot{\tau}_i \in -1 + \rho \mathbb{B}$$

► Rate uncertainty

$$[T_1^i, T_2^i] \quad \rightarrow \quad [T_1^i - \rho, T_2^i + \rho]$$

► Unmodeled dynamics

► Additive dynamics

$$\dot{z}_i = f_i(z_i, u_i) \quad \rightarrow \quad \dot{z}_i \in f_i(z_i, u_i) + \rho \mathbb{B}$$

► Event conditions

$$\tau_i = 0 \quad \rightarrow \quad \tau_i \in \rho \mathbb{B}$$

► Disturbances

► Actuator noise (ISS)


► Measurement noise (ISS)

Conclusion


- ▶ Introduction to Hybrid Systems and Modeling for Control of Networks
- ▶ Control Design via Lyapunov and its Relaxations
- ▶ Nominal Robustness via Checkable Properties
- ▶ Applications and Current Projects

Future Directions:


- ▶ Temporal logic
- ▶ Optimality conditions
- ▶ Hybrid games
- ▶ Computation-based learning



IEEE 2009



Princeton U. Press
2012



CRC Press 2015

Conclusion


- ▶ Introduction to Hybrid Systems and Modeling for Control of Networks
- ▶ Control Design via Lyapunov and its Relaxations
- ▶ Nominal Robustness via Checkable Properties
- ▶ Applications and Current Projects

References at hybrid.soe.ucsc.edu


Thank you for your attention!

*Research funded by AFOSR, AFRL, CITRIS, Honeywell,
Mathworks, and NSF*

One-day Workshop @ 2016 CDC in Las Vegas
One-week Course @ 2017 EECI-IGSC in Paris




IEEE 2009



Princeton U. Press

2012



CRC Press 2015